J

V

# Comercial J. Velasco

Correo: comercial-jvelasco@gmail.com

Movil: +34 606-42-12-18

## L-188 Re-Printable U.V Varnish

#### Description

**L-188** is re-printable type UV varnish for paper coating industry. The difference between S-188 and L-188 is only on film surface, for L-188, it can be further processed by applying glue and metal-foil for special purpose, but S-188 can't.

#### **Product Specifications**

Appearance/Color	light yellow liquid
Viscosity (Ford Cup #4, 25°C)	45 ± 2 sec
Curing speed	30M/min/Lamp (80w / per-cm²)
Gloss 60°	80 ± 5

### Safety and Notes

- (1) Storage: keep away from high temperature, high humidity and direct sun-light'; keep tightly closed while storing.
- (2) Product expiration: sealed, 12 months.
- (3) This product is non self-ignition, corrosive and explosive. For risk, wear mask and gloves while using and handling, and keep watch to prevent touching and breathing. If skin is contacted, promptly and thoroughly flush skin with plenty of water use soap if available. If irritation persists, seek medical attention. If eye is contacted, rinse eyes immediately with large amounts of water (or 0.9% sterile salt solution)for at least 15 minutes and contact physician as needed.(S26)
- (4) Fire point: 102°C (method: ASTM D92). Fire fighting material: foam or CO₂ extinguisher.

#### **Package**

20Kg, 200Kg plastic drum

(REFERENCE ONLY)