J

V

Comercial J. Velasco

Correo: comercial-jvelasco@gmail.com

Movil: +34 606-42-12-18

S-1883N U.V Varnish

Description

S-1883N is UV varnish for paper coating industry. It has high curing speed and excellent film properties such as good adhesion, flexibility, scratch resistance and high gloss. It can also be applied to gloss overprint varnish for stick labels or book covers.

Product Specifications

Appearance	light yellow Liquid
Color (Gardner)	2 max
Viscosity (25°C,Brookfield LVT)	1400 ± 200
Curing speed	30M/min/Lamp (80W / per-cm²)
Gloss 60°	> 95

Safety and Notes

- (1) Storage: keep away from high temperature, high humidity and direct sun-light'; keep tightly closed while storing.
- (2) Product expiration: sealed, 12 months.
- (3) This product is non self-ignition, corrosive and explosive. For risk, wear mask and gloves while using and handling, and keep watch to prevent touching and breathing. If skin is contacted, promptly and thoroughly flush skin with plenty of water use soap if available. If irritation persists, seek medical attention. If eye is contacted, rinse eyes immediately with large amounts of water (or 0.9% sterile salt solution)for at least 15 minutes and contact physician as needed.(S26)
- (4) Fire point: 102°C (method: ASTM D92). Fire fighting material: foam or CO₂ extinguisher.

Package

20Kg plastic drum, 200Kg iron drum

(REFERENCE ONLY)