J

V

# Comercial J. Velasco

Correo: comercial-jvelasco@gmail.com

Movil: +34 606-42-12-18

## S-189 Low Viscosity U.V Varnish

#### Description

S-189 is an epoxy acrylic-based UV varnish for paper coating industry. It has high curing speed and excellent film properties such as good hardness and high gloss. It can also be applied to gloss overprint for labels and book covers.

#### **Specifications**

Appearance/Color	light yellow Liquid
Viscosity(Ford Cup #4, 25°C)	25 ± 5 sec
Curing speed	30 M/min/Lamp (80W/cm²)
Gloss 60°	85 ± 5

#### Safety and Notes

- (1) Storage: keep away from high temperature, high humidity and direct sun-light; keep tightly closed while storing.
- (2) Product expiration: sealed, 12 months.
- (3) This product is non self-ignition, corrosive and explosive. For risk, wear mask and gloves while using and handling, and keep watch to prevent touching and breathing. If skin is contacted, promptly and thoroughly flush skin with plenty of water use soap if available. If irritation persists, seek medical attention. If eye is contacted, rinse eyes immediately with large amounts of water (or 0.9% sterile salt solution)for at least 15 minutes and contact physician as needed.(S26)
- (4) Fire point: 102°C (method: ASTM D92). Fire fighting material: foam or CO₂ extinguisher.

### **Package**

20Kg, 200Kg plastic drum

(REFERENCE ONLY)